



Versafit

Versafit is a highly flame retarded, very flexible heat-shrink tubing designed to meet the stringent requirements of UL224 VW-I and CSA-OFT. It is ideal for very flexible, lightweight harnesses which require the highest level of flame retardancy. Versafit is often used in commercial electronics and telecommunication systems. Versafit has a low shrink temperature reducing installation time and the risk of damage to temperature sensitive components.

Raychem

Technical Characteristics

| | |
|-----------------------------------|-----------------|
| Continuous operating temperature | -55°C to +135°C |
| Minimum full recovery temperature | +90°C |
| Shrink ratio | 2:1 |

Part Numbering Information

| Part No | D (mm) | d (mm) | W (mm) |
|---------------------------|-----------|-----------|-----------|
| Versafit - 3/64 - Colour | 1.63 | 0.58 | 0.40 |
| Versafit - 1/16 - Colour | 1.85 | 0.79 | 0.43 |
| Versafit - 3/32 - Colour | 2.79 | 1.17 | 0.51 |
| Versafit - 1/8 - Colour | 3.43 | 1.57 | 0.51 |
| Versafit - 3/16 - Colour | 5.21 | 2.36 | 0.51 |
| Versafit - 1/4 - Colour | 7.11 | 3.17 | 0.64 |
| Versafit - 3/8 - Colour | 10.16 | 4.74 | 0.64 |
| Versafit - 1/2 - Colour | 13.72 | 6.35 | 0.64 |
| Versafit - 5/8 - Colour | 16.90 | 8.00 | 0.76 |
| Versafit - 3/4 - Colour | 20.45 | 9.52 | 0.76 |
| Versafit - 1 - Colour | 25.53 | 12.70 | 0.89 |
| Versafit - 1-1/2 - Colour | 39.88 | 19.05 | 1.02 |
| Versafit - 2 - Colour | 52.83 | 25.40 | 1.14 |
| Versafit - 3 - Colour | 78.49 | 38.10 | 1.27 |
| Versafit - 4 - Colour | 104.14 | 50.80 | 1.40 |

Availability

Standard colours: Black (0)
Other colours available

Specifications: UL E35586 VW-I
CSA LR31929 OFT
AMS-DTL-23053/5 Classes 1+3

Note: Former Cabletec part description: GUL
Also available in 3:1 shrink ratio

