



# ZH-100

ZH-100 is a flexible, thin-wall, heat-shrink tubing designed for low-fire-hazard applications. ZH-100 contains no added halogens and exhibits excellent fire safety characteristics combined with low evolution of acid gases, while retaining good mechanical and fluid resistance properties. ZH-100 is available in a variety of colours.

**Raychem**



## Technical Characteristics

Continuous operating temperature	-30°C to +105°C
Minimum full recovery temperature	+120°C
Shrink ratio	2:1

## Part Numbering Information

Part No	D (mm)	d (mm)	W (mm)
ZH-100 - 1/8 - Colour	3.2	1.6	0.50
ZH-100 - 3/16 - Colour	4.8	2.4	0.50
ZH-100 - 1/4 - Colour	6.4	3.2	0.65
ZH-100 - 3/8 - Colour	9.5	4.8	0.65
ZH-100 - 1/2 - Colour	12.7	6.4	0.65
ZH-100 - 3/4 - Colour	19.0	9.5	0.75
ZH-100 - 1 - Colour	25.4	12.7	0.90
ZH-100 - 1-1/2 - Colour	38.0	19.0	1.00
ZH-100 - 2 - Colour	51.0	25.4	1.15

## Availability

Standard colours: Black (0)  
 Non-standard colours: White (9), Red (2), Blue (6), Yellow (4), Green (5)

Specifications: BR1326  
 Flammability UL224  
 Def Stan 59-97 Type 8  
 BS 4G-198 Part 3 Type 15

