

# HT-SCE Markers

HT-SCE heat-shrink markers are specifically designed for high temperature applications or where extreme resistance to fuels, lubricants or cleaning solvents is required. HT-SCE markers have very low vacuum out-gassing properties and as such are ideal for use on-board satellites. They are extremely tough and abrasion resistant and are very highly flame retarded. HT-SCE markers are fully compatible with the System Six range of printers and WinTotal software.

## Raychem

### Technical Characteristics

Continuous operating temperature	-55°C to +225°C
Shrink ratio	2:1 (3:1 on 3/32 size)
Printing options	Dot matrix and thermal transfer

### Part Numbering Information

Part No	Supplied Inside Diameter (mm)	Recovered Inside Diameter (mm)	Sleeve Length (mm)
HT-SCE - 3/32 - Colour	2.4	0.79	50
HT-SCE - 1/8 - Colour	3.2	1.6	50
HT-SCE - 3/16 - Colour	4.8	2.4	50
HT-SCE - 1/4 - Colour	6.4	3.2	50
HT-SCE - 3/8 - Colour	9.5	4.8	50
HT-SCE - 1/2 - Colour	12.7	6.4	50
HT-SCE - 3/4 - Colour	19.1	9.5	50
HT-SCE - 1 - Colour	25.4	12.7	50
HT-SCE - 1-1/2 - Colour	38.1	19.1	50

### Availability

Standard colours: White (9) and Black (0)  
Pack sizes: 250 and 1000 (1K)

Specifications: MIL-M-81531 & MIL-STD-202F method 215J (Print permanence)  
UL VW-1

**Note:** For marked product add (M) to part number i.e. HT-SCE-3/32-9(M)  
For pre-scored product add S1, S2 or S3 to part number i.e. HT-SCE-3/32-S1-9 for 1 score

### FULL PRINTING AND KITTING SERVICE AVAILABLE

**cabletec**